

Pemulwuy

Pemulwuy Options



H 2265-1 B

BENEFITS

Precise temperature controls from 30 °C to 250 °C
8 operating modes

DESIGN

Obsidian Black appliance with stainless steel fascia panel and handle

CONTROLS

EasyControl with retractable dials and 7-segment LCD with touch sensors

APPLIANCE DOOR

CleanGlass oven door
Triple glazing

APPLIANCE INTERIOR

76 l oven with 5 rack levels
Removable side racks
Halogen lighting

CLEANING AND CARE

Stainless steel front with CleanSteel finish
Enamelled oven interior with PerfectClean finish
Catalytically self-cleaning rear liner
Hinged grill

SAFETY

Cooling system
Touch-cool front
Safety switch-off

ECONOMY

Rapid heat-up for up to 50% shorter preheating time

STANDARD ACCESSORIES

Multi-purpose tray with PerfectClean finish
Baking and Roasting rack

DA 2390

90 cm wide,
extra-slim design,
light-touch controls with LEDs,
4 x 3 W LED lights,
air flow up to 600 m³/h in booster setting

KM 2054 G

Design

Stainless steel gas hob unit
Removable cast iron grates in matt black
Integrated controls
Solid metal knobs

User convenience

Front knob controls

Heating

5 gas rings for natural gas and liquid gas

Power rating**

Front left: Dual wok, 0.25–4.20 kW

Rear left: Simmer burner, 0.27–1.00 kW

Middle: High speed burner, 0.45–2.60 kW

Rear right: Dual wok, 0.25–4.20 kW

Front right: Standard burner, 0.38–1.75 kW

Recommended pan base diameters:

Simmer burner: 100–220 mm

Standard burner: 120–220 mm

High speed burner: 140–240 mm

Dual wok: 160–260 mm

Features

Single-handed electronic ignition

Safety

Thermoelectric ignition monitoring

Standard accessories

Wok ring

Separate jets for liquid gas

Electrical connection

230 V, 50 Hz, total connected load <25 W

Cut-out dimensions

Width: 860 mm

Depth: 480–490 mm